

Whole House Humidifiers

Reduces static electricity

Lowers heating bills & saves energy

Protects woodwork and furniture

Uses 40% less water than competitive brands

A humidifier solution that services the entire house

Attaches directly to HVAC system

HE360A

Power Flow Through Duct Mounted Humidifier

- 18 gal./day up to 4,200 sq. ft.
- Easiest installation – great for tight spaces
- Best for variable speed system
- PerfectFlo™ water distribution tray



HE220A, HE260A


By-Pass Flow Through Duct Mounted Humidifiers

- HE220A – 12 gal./day up to 3,000 sq. ft.
- HE260A – 17 gal./day up to 4,000 sq. ft.
- Most popular models
- Easy mounting on forced air furnace
- PerfectFlo™ water distribution tray




See back for detailed features and product specifications

Features:




HE360A Power Flow Through Duct Mounted

- Easiest installation – no by-pass duct required. Mount on supply.
- Flow-through design helps keep unit clean of micro-organisms and decreases the frequency of maintenance.
- Best for variable speed systems.



HE260A By-Pass Flow Through Duct Mounted

- Flow-through design helps keep unit clean of micro-organisms and decreases the frequency of maintenance.
- Easy mounting on either warm air supply or return air duct of any forced air furnace.



HE220A By-Pass Flow Through Duct Mounted

- Flow-through design helps keep unit clean of micro-organisms and decreases the frequency of maintenance.
- Easy mounting on either warm air supply or return air duct of any forced air furnace.

Specifications:

Model	HE360A	HE260A	HE220A
Master Carton Qty	1	1	1
Dimensions (in.)	14.55" W x 21.28" H x 17.28" D	20.90" W x 15.68" H x 12.15" D	17.90" W x 14.77" H x 12.15" D
Carton Weight (lbs.)	18.5	10.3	9.3
Cu. Ft.	3.1	2.3	1.9
Retail Package Qty	1	1	1
Dimensions (in.)	14.55" W x 21.28" H x 17.28" D	20.90" W x 15.68" H x 12.15" D	17.90" W x 14.77" H x 12.15" D
Carton Weight (lbs.)	18.5	10.3	9.3
Cu. Ft.	3.1	2.3	1.9

Model	HE360A	HE260A	HE220A
Capacity*	18 gal./day up to 4,200 sq. ft.	17 gal./day up to 4,000 sq. ft.	12 gal./day up to 3,000 sq. ft.
Drain Required	Yes	Yes	Yes
Typical Humidification Area			
Loose(2 air chg/hr)	1,900 sq. ft.	1,000 sq. ft.	750 sq. ft.
Average(1 air chg/hr)	2,700 sq. ft.	2,000 sq. ft.	1,500 sq. ft.
Tight(1/2 air chg/hr)	4,200 sq. ft.	4,000 sq. ft.	3,000 sq. ft.
Electrical Rating	120Vac, 0.7A	24Vac, 0.5A	24Vac, 0.5A
Dimensions W x H x D (in/mm)	14 x 15.25 x 10.25 / 356 x 387 x 260	13.562 x 16.75 x 9.25 / 345 x 425 x 235	12 x 13.562 x 9.125 / 305 x 345 x 232
Plenum Duct Opening W x H x D (in/mm)	13.5 x 14.062 / 343 x 357	9.75 x 12.625 / 248 x 321	9.312 x 9.437 / 238 x 241
Bypass Duct Opening (in/mm)	NA	6(152)	6(152)
Replacement Pad	HC26A1008	HC26A1008	HC22A1007

*Capacity measured at 120°F plenum temp – 0.20 Static Pressure Drop (gal./day)

Package UPC (US):



Package UPC (Canada):

